

## CS Series CSC46

The CS 4 x 6 Inch Coaxial Speakers are an excellent factory upgrade.

A stamped steel framework supports a rigid polypropylene cone for excellent audio quality. Using zero protrusion PEI tweeters ensures you get every bit of detail you need, without interfering with factory grilles.

These CS speakers work best with 50 watts of recommended power. See below for more details.



## Specifications

### Speaker Design

2 - way

### Woofer Size | in [mm]

4x6 [100x160]

### Tweeter Size | in [mm]

1/2 [13]

### DC Resistance | ohm

3.3

### Peak Power | Watts

150

### Continuous Power | Watts, RMS

50

### Sensitivity [SPLo] | dB @ 1W, 1m

88

### Effective Frequency Range | Hz

50-20k

### Mounting Hole Diameter | in [mm]

4 x 6 [101x152]

### Top Mount Depth | in [mm]

5/16 [7]

### Bottom Mount Depth | in [mm]

1 11/16 [43]

### Tweeter Protrusion | in [mm]

0

### Grilles

No

### Tweeter Magnet Material

Neodymium

### Tweeter Dome Material

PEI [polyether imide]

### Tweeter Design

Balanced dome

### Woofer Cone Material

Polypropylene

### Woofer Surround Material

Polyester foam