

CS Series CSC693

The CS 6x9-Inch Triaxial (Three-Way) Speakers are an excellent factory upgrade.

A stamped steel framework supports a rigid polypropylene cone with EVC™ (Extended Voice Coil) technology, for the best sonic quality. Using zero protrusion PEI tweeters ensures you get every bit of clarity you need, without interfering with factory grilles. Adding a CX amplifier will give you even more power and clarity to your system.

These CS speakers work best with 150 watts of recommended power. See below for more details.



Specifications

Speaker Design

3 - way

Woofer Size | in [mm]

6x9 [160x230]

Mid Size | in [mm]

2 [50]

Tweeter Size | in [mm]

1/2 [13]

DC Resistance | ohm

3.5

Peak Power | Watts

450

Continuous Power | Watts, RMS

150

Sensitivity [SPLo] | dB @ 1W, 1m

92

Effective Frequency Range | Hz

30-20k

Mounting Hole Diameter | in [mm]

5 5/8 x 8 7/16 [143x215]

Top Mount Depth | in [mm]

7/16 [12]

Bottom Mount Depth | in [mm]

3 3/16 [81]

Tweeter Protrusion | in [mm]

1/16 [1]

Grilles

Yes

Tweeter Magnet Material

Electric Crystal Motor

Tweeter Dome Material

PEI [polyether imide]

Tweeter Design

Balanced dome

Woofer Cone Material

Polypropylene

Woofer Surround Material

Polyester foam

