

POWERBASS

XL SERIES SUBWOOFERS

UP TO
800
WATTS

Proprietary 4-layer, Non-pressed Paper, DDC Finish Cone (Dynamic Damping Coating) for deeper, distortion free bass

Proprietary Composite Polycarbonate/Glass Fiber Basket turbine design provides a rigid and stable woofer platform

Dual and Single 4-ohm Voice Coils made with high temperature cooper winding for optimum power handling
2" Vented BASV Voice Coil Formers for optimal performance and power handling

High Roll Santoprene Surround increases cone area and maximizes excursion while providing exceptional linear stability

Xtra Large Motor Structures for increased SPL and power handling

Spring Loaded Nickel Plated Input Terminals ensure maximum current transfer from your amplifier to your subwoofer

Optimally Designed for Both Sealed or Ported Enclosures for multiple installation applications



Order Desk: Orders@BBDistribution.ca

XL1244D

12" Dual 4 Ohm Voice Coil Subwoofer 400W RMS/800W Max, 5.7" Mount Depth.

XL1244

12" Single 4 Ohm Voice Coil Subwoofer 400W RMS/800W Max, 5.7" Mount Depth.

XL1044D

10" Dual 4 Ohm Voice Coil Subwoofer 350W RMS/700W Max 5.25" Mount Depth.

XL1044

10" Single 4 Ohm Voice Coil Subwoofer 350W RMS/700W Max 5.25" Mount Depth.

XL844D

8" Dual 4 Ohm Voice Coil Subwoofer 200W RMS/400W Max 4.4" Mount Depth.

XL844

8" Single 4 Ohm Voice Coil Subwoofer 200W RMS/400W Max 4.4" Mount Depth.



www.BBDistribution.ca |